

WAVE POWER ADVANTAGE LE 5W-40

Fully Synthetic Passenger Car Engine oil

WAVE POWER ADVANTAGE LE 5W-40 is a cost effective fuel saving MID SAPS technology and used in light duty vehicles fitted with direct injection, turbocharges and after-treatment systems, gasoline catalytic converter, or diesel particulate filter technology.

WAVE POWER ADVANTAGE LE 5W-40 is based on high performance base oils in combination with a specially selected additive technology to ensure the following properties:

- Strong Fuel Economy Performance
- Excellent Engine Durability
- Excellent Engine Compatibility
- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Good low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.

WAVE POWER ADVANTAGE LE 5W-40 meets the following performance criteria:

Meets API SP ACEA C3 MB 229.31 MB 229.51

Suitable API SN/CF Dexos 2 <- 2019 BMW LL-01 applications

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-40
Density @15 °C	kg/m ³	ASTM D4052	849
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	83.9
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.0
Viscosity Index		ASTM D2270	173
Viscosity CCS @ -30 °C	cP	ASTM D5293	6180
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.1
Sulphated Ash	%Wt	ASTM D874	0.8
Date Issued: 22-3-2022		Supersedes: 12-04-2021	Revision Nr.: 01

