

WAVE POWER PERFORMANCE 10W-40

Semi Synthetic Passenger Car Engine oil

WAVE POWER PERFORMANCE 10W-40 is an universal high performance semi synthetic oil for use in gasoline- and diesel engines of passenger cars and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

WAVE POWER PERFORMANCE 10W-40 is formulated with high quality re-refined base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- High thermal and oxidation stability.
- Good resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High Viscosity Index.

WAVE POWER PERFORMANCE 10W-40 meets the following performance criteria:

API SL/CF

Typical Analysis

Properties	Unit	Method	Typical Value
Colour		ASTM D1500	2.5
SAE Grade		SAE J300	10W-40
Density @15 °C	kg/m ³	ASTM 4052	856
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	93
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.4
Viscosity Index		ASTM D2270	161
Viscosity CCS @ -25 °C	cP	ASTM D5293	4500
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.6
Sulphated Ash	%Wt	ASTM D874	1.05
Date Issued: 25-03-2021		Supersedes: 22-03-2019	Revision Nr.: 02

