

WAVE POWER EXCELLENCE 15W-40

Mineral Passenger Car Engine oil

WAVE POWER EXCELLENCE 15W-40 is a high quality mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

WAVE POWER EXCELLENCE 15W-40 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

WAVE POWER EXCELLENCE 15W-40 meets the following performance criteria:

API SP

ACEA A3/B4

VW 501.01/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15 °C	kg/m ³	ASTM 4052	859
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	93.6
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.0
Viscosity Index		ASTM D2270	154
Viscosity CCS @ -20 °C	cP	ASTM D5293	3800
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	10.9
Sulphated Ash	%Wt	ASTM D874	1.3
Date Issued: 27-01-2023		Supersedes: 24-06-2021	Revision Nr.: 03

