

## TIDAL POWER LA 30

### High Performance Heavy Duty Gas Engine Oil

**TIDAL POWER LA 30** is a Low Ash high performance heavy duty gas engine oil specially designed for use in stationary gas engines which run on natural and/or biogas and operate under severe conditions and high temperatures.

**TIDAL POWER LA 30** is based on high-quality hydro processed base oils in combination with a special selected additive package to obtain the following properties:

- Excellent thermal-, nitration-, and oxidation stability.
- Reducing of combustion chamber deposits.
- Minimize ring scuffing.
- Protect against corrosive wear.
- Improving engine performance.

**TIDAL POWER LA 30** meets the following performance criteria:

GE Jenbacher for Fuel Class A (Natural gas) and B (Biogas), Type 2 and 3 all engines; Type 4, Version A, B; Type 6 up to version E

API CF

Waukesha Cogeneration

Dresser Rand Category III

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	30
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	880
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	96
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	11.3
Viscosity Index		ASTM D2270	95
Flash Point COC	°C	ASTM D92	>215
Pour Point	°C	ASTM D7346	-15
Total Base Number	mgKOH/g	ASTM D2896	5.6
Sulphated Ash	%Wt	ASTM D874	0.49
Date Issued: 16-6-2021	Supersedes: 11-02-2016	Revision Nr.: 01	

