

AUTOGEAR POWER MP 80W-90

Automotive Multi Purpose Gear Oil

AUTOGEAR POWER MP 80W-90 is a high performance multi purpose gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives.

AUTOGEAR POWER MP 80W-90 is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

AUTOGEAR POWER MP 80W-90 meets the following performance criteria:

API GL-5 MIL-L-2105D MAN 342 M1 MAN 342 M2
MB 235.0 Volvo 1273.10 ZF TE-ML 05A, 07A, 16B/C/D, 17B, 19B, 21A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W-90
Density @15°C	kg/m ³	ASTM 4052	889
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	134
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	14.4
Viscosity Index		ASTM D2270	104
Viscosity Brookfield @-26°C	cP	ASTM D5293	200000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-34
Date Issued: 22-01-2021		Supersedes: 08-11-2018	Revision Nr.: 02

