

## AUTOGEAR POWER MP 80W-140

### Automotive Gear Oil

**AUTOGEAR POWER MP 80W-140** is a high-performance gear lubricant for use in heavy duty manual transmissions and axle drives of commercial vehicles and passenger cars.

**AUTOGEAR POWER MP 80W-140** is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR POWER MP 80W-140** meets the following performance criteria:

API GL-5                      MB 235.0                      MIL-L-2105D                      MAN 342 M1  
Volvo 97310                      Volvo 97316                      Voith 3.325-339  
ZF TE-ML 07A, 08, 16B/C/D, 17B, 19B, 21A

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W-140
Density @15°C	kg/m <sup>3</sup>	ASTM 4052	894
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	254
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	27.9
Viscosity Index		ASTM D2270	145
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-36
Date Issued: 16-6-2021	Supersedes: 03-08-2016	Revision Nr.: 01	

