

AUTOGEAR POWER MTF 75W-80

Manual transmission fluid

AUTOGEAR POWER MTF 75W-80 is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions and transaxles. Not suitable for differentials and other API GL-5 applications.

AUTOGEAR POWER MTF 75W-80 is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

AUTOGEAR POWER MTF 75W-80 meets the following performance criteria:

API GL-4	BMW MTF LT-2	BMW MTF LT-3	BMW MTF LT-4
Ford WSD-M2C200-C	GM 1940182	GM 1940764	GM 1940768
GM 1940004	GM 19259104	Ford WSS-M2C200-D2	MB 235.10
PSA B71 2330	MTF 94	Honda MTF	Honda MTF-II/III
Nissan MT-XZ	Nissan MT-XZ TL	Volvo 97308	Volvo 97309
VW G 009 317	VW G 052 171	VW G 052 178	VW G 052 512
VW G 052 527	VW G 052 726	VW G 060 726	VW G 070 726
VW G50	Renault (NFJ/NFP/TRJ/TRT/TRZ)		

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W-80
Density @15°C	kg/m ³	ASTM 4052	862
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	51.2
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	9.3
Viscosity Index		ASTM D2270	165
Brookfield Viscosity @-40°C	cP	ASTM D2983	<75000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Date Issued: 16-6-2021	Supersedes: 27-02-2018	Revision Nr.: 03	

