

HYDRA POWER SYNTH 32

Fully Synthetic Hydraulic Oil

HYDRA POWER SYNTH 32 is a premium quality ashless fully synthetic environmentally acceptable hydraulic oil specially developed to meet the requirements of the most demanding modern hydraulic systems in industrial and mobile services.

HYDRA POWER SYNTH 32 is based on high quality synthetic base oil in combination with an unique additive package to ensure the following properties:

- Outstanding thermo-oxidative stability reduces deposit formation, improves pump & valve performance and allows extension of oil and filter change intervals.
- Exceptional anti-wear property.
- Naturally High Viscosity Index ensures minimum viscosity change over a wide temperature range.
- Excellent demulsibility helps in faster separation of water from oil and resists formation of emulsions.
- Special rust & corrosion inhibitors protect multi-metallurgy components against negative effects of moisture presence in the system.
- Rapid air release property due to non-silicone anti-foam technology to minimizes chances of pump cavitations leading to trouble free operations.
- Offers long term hydrolytic stability and yellow metal compatibility in presence of water.
- Compatible with multi-metals and sealing materials commonly used in hydraulic systems.

HYDRA POWER SYNTH 32 meets the following performance criteria:

DIN 51524/2 HLP
I-286-S

AFNOR NFE 48-603
US Steel 127, 136

ISO 11158 HMVickers M-2950-S
Denison HF-0

Cincinnati P-68

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	32
Density @15°C	kg/m ³	ASTM D4052	833
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	31
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.0
Viscosity Index		ASTM D2270	141
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-66
FZG Fail Load Stage, min		DIN 51354-2	11
Demulsibility @54°C	Minutes	DIN 51599	5
Date Issued: 14-6-2021		Supersedes: 17-10-2016	Revision Nr.: 01

