

## WAVE POWER PERFORMANCE 5W-40

### Semi-Synthetic Passenger Car Motor Oil

**WAVE POWER PERFORMANCE 5W-40** is an universal high performance fuel saving oil based on semi-synthetic technology for use in gasoline engines of passenger car and light vans with or without turbocharger.

**WAVE POWER PERFORMANCE 5W-40** is formulated with high quality hydro-treated mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

**WAVE POWER PERFORMANCE 5W-40** is suitable for use where the following specifications are required:

API SN/CF

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-40
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	849
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	84.05
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	14.40
Viscosity Index		ASTM D2270	179
Viscosity CCS @ -30 °C	cP	ASTM D5293	4205
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.2
HTHS 150 °C	mPa.s	ASTM D4683	3.8
Date Issued: 2-3-2022	Supersedes:	Revision Nr.:	

