

UNIVERSAL TRACTOR POWER 102

Universal Tractor Transmission Oil (UTTO)

UNIVERSAL TRACTOR POWER 102 is a low-viscosity, fuel saving, high performance fluid for use in (CVT) transmissions, hydraulic systems, oil immersed brakes of tractors and off-road equipment. These fluids are specially designed for use where a common lubricant reservoir serves transmissions, final drives and hydraulic systems and to optimize the performance of agricultural and commercial tractors.

UNIVERSAL TRACTOR POWER 102 is based on high quality synthetic base oil in combination with an unique additive package to ensure the following properties:

- High oil aging resistance due to its synthetic base oils, allowing high drain intervals
- Enhanced frictional properties optimize clutch performance and ensure noise free operation of wet brakes
- High viscosity index coupled with high shear stability provides consistent performance
- Excellent low temperature fluidity provides good response and effective lubrication at low ambient temperatures
- Robust anti-wear and extreme pressure properties control wear, extend equipment life and reduce maintenance costs
- Multipurpose capability reduces inventory and prevents accidental contamination and misapplication

UNIVERSAL TRACTOR POWER 102 meets the following performance criteria:

Volvo WB102

Volvo 97304

JDM 20C, JDM 20D

API GL-4

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W75
Density @15°C	kg/m ³	ASTM 4052	856
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	35
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	191
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	12
Date Issued: 08-03-2024	Supersedes:	Revision Nr.: 01	

