

WAVE POWER SPECIAL ASP 5W-30

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER SPECIAL ASP 5W-30 is a high-performance fuel saving MID SAPS engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines, with and without particle filter, of passenger cars and light vans where a PSA B71 2290 specification is required and suitable for all engines which require an ACEA A5/B5 performance specification.

WAVE POWER SPECIAL ASP 5W-30 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

WAVE POWER SPECIAL ASP 5W-30 meets the following performance criteria:

Meets API SP ACEA C2/C3 PSA B71 2290

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15 °C	kg/m ³	ASTM 4052	853
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	66.3
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	11.5
Viscosity Index		ASTM D2270	169
Viscosity CCS @ -30 °C	cP	ASTM D5293	6093
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	9.5
Date Issued: 08-03-2024	Supersedes: 08-03-2024	Revision Nr.: 04	

