

## SNOWMOBILE POWER 2T

### Fully Synthetic 2-Stroke Snowmobile Oil

**SNOWMOBILE POWER 2T** is a supreme performance synthetic lubricant specially developed for high output air and liquid cooled 2-stroke snowmobiles, which are operating under severe conditions. SNOWMOBILE POWER 2T is also suitable for all 2-Stroke chainsaw engines.

**SNOWMOBILE POWER 2T** is based on high quality fully synthetic (ester) base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional protection against piston scuffing and wear of engine components.
- Exceptional control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Low ash additive technology prevents pre-ignition and spark plug.
- Easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

**SNOWMOBILE POWER 2T** meets the following performance criteria:

API TC      JASO FD      ISO-L-EGD      TISI      Rotax (253)      Husqvarna (272)

### Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	875
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	54.3
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	9.7
Viscosity Index		ASTM D2270	166
Flash Point COC	°C	ASTM D92	108
Pour Point	°C	ASTM D7346	-51
Total Base Number	mgKOH/g	ASTM D2896	1.9
Sulphated Ash	%Wt	ASTM D874	0.14
Date Issued: 25-09-2024	Supersedes: -	Revision Nr.: -	

